

TECHNICAL DATA

DUAL STAGE ROTARY VANE 2010 C2

- Dual Stage Pump
- Universal Motor 115-245 VAC 50/60hz
- Replaceable shaft seal without dismantling
- Less air contamination & low oil consumption
- Alignment pins on pump module
- Designed for the best answer to the most aggressive pumping environments. They incorporate specific anti corrosion features for improved reliable operations.



ADIXEN

PASCAL C2

Units 2010C2

Nominal pumping speed (*)	50Hz	m ³ /h	9.7
	60Hz	cfm	6.8
Pneurop pumping speed (*)	50Hz	m ³ /h	8.5
	60Hz	cfm	6
Ultimate partial pressure (*)		mbar	5.10 ⁻⁴
Ultimate total pressure (*) closed gas ballast		mbar	3.10 ⁻³
Weight (max)		kg (lbs)	26 (57.2)
Max nominal power rating 50/60Hz		kW	0.45/0.55
Min ambient temperature		°C (°F)	12 (54)
Max ambient temperature		°C (°F)	45 (113)
Oil Capacity		l	0.95
Inlet Flange		ISO-KF	DN25
Exhaust Flange		ISO-KF	DN25

Specially designed for the most aggressive pumping environments.
Factory Prepared With PFPE A113 Oil.

Brand **NEW** Comes With
Manufacture Warranty

Recommended Oil for this Alcatel Vacuum Pump is PFPE Alcatel A113 Synthetic Oil. Sold in Kilograms on this Website.



THIS UNIT IS NEW AND COMES WITH MANUFACTURE WARRANTY