



- NOTES:
1. ROTARY SPEED: <13900RPM
 2. VACUUM BASE: 10^{-8} Torr
 3. VACUUM LEAK CHECK TO LESS THAN 10^{-12} Pa.M³/sec HELIUM
 4. DIFFERENTIAL PRESSURE: 1Kg/cm²
 5. TEMPERATURE: 0-80°C
 5. GASES SEALED: INERT GASES

UNRELEASED
 PENDING CUSTOMER APPROVAL
 Approved _____ Date _____

普通許容差			NUB	NUB	CONTENT	NAME	PREPARED	JUDY	6.3	1.6
加工種別	用り	プレス					3-18-04			
寸法区分	一般	穴磨	一般				CHECKED DATE	KOBAYASHI	MATL	HOUSING SUS304
	6以下	±0.1	±0.15	±0.5			ENGINEER DATE	3-18-04		SHAFT SUS420
	6*最大	30 *	±0.2				MFC, ENG DATE			
	30 *	120 *	±0.3	±0.2	±0.7					
	120 *	315 *	±0.5	±0.25	±1.0					
	315 *	1000 *	±0.8	±0.4	±1.5					
	1000 *	2000 *	±1.2	±0.6	±2.0					

FEEDTHROUGH		Model	
STB012NN		P/N	
SCALE	REV		
1/1	Z		