



- NOTES:
1. ROTARY SPEED: $\lt; 13900\text{RPM}$
 2. VACUUM BASE: 10^{-8} Torr
 3. VACUUM LEAK CHECK TO LESS THAN 10^{-12} Pa.M³/sec HELUUM
 4. DIFFERENTIAL PRESSURE: 1Kg/cm²
 5. TEMPERATURE: 0-80°C
 5. GASES SEALED: INERT GASES

UNRELEASED
 PENDING CUSTOMER APPROVAL
 Approved _____ Date _____

普通許容差				加工種別	寸法区分	NUB	NUB	CONTENT	NAME	PREPARED	JUDY 3-18-04	CHECKED KOBAYASHI 3-18-04	DATE	ENGINEER DATE	MFC, ENG DATE	MATERIAL	HOUSING: SUS304 SHAFT: SUS420
削リ	プレス	一般	穴間														
6以下	±0.1	±0.15	±0.5														
6を越え 30	±0.2	±0.15	±0.5														
30	120	±0.3	±0.2	±0.7													
120	315	±0.5	±0.25	±1.0													
315	1000	±0.8	±0.4	±1.5													
1000	2000	±1.2	±0.6	±2.0													

Model: FEEDTHROUGH
 STB012NN

P/N: _____

SCALE: 1/1

REV: Z

PROJECTION: