



NOTES:

- 1. ROTARY SPEED: <18200RPM (NO LOAD)
- 2. VACUUM BASE: 10^{-8} Torr
- 3. VACUUM LEAK CHECK TO LESS THAN 10^{-12} Pa.M³/sec HELIUM
- 4. DIFFERENTIAL PRESSURE: 1Kg/cm²
- 5. TEMPERATURE: 0-80°C
- 5. GASES SEALED: INERT GASES

UNRELEASED
 PENDING CUSTOMER APPROVAL
 Approved _____ Date _____

普通許容差				NUB	NUB	CONTENT	NAME	PREPARED	JUDY 3-1-01	6.3/1.6	Model	FEEDTHROUGH SNB006NN	P/N	SCALE	REV
加工種?	前リ	プレス	一般												
寸法区分	6以下	±0.1	±0.15	±0.5				CHECKED	KOBAYASHI	MATL	HOUSING SUS304 SHAFT SUS630			1/1	D
	6~30	±0.2	±0.2	±0.7				DATE	3-2-01						
	30 ~ 120	±0.3	±0.2	±0.7				ENGINEER							
	120 ~ 315	±0.5	±0.25	±1.0				DATE							
	315 ~ 1000	±0.8	±0.4	±1.5				MFC, ENG							
	1000 ~ 2000	±1.2	±0.6	±2.0				DATE							

